ACACIA COMMUNITY III

BUILDING SPECIFICATIONS

FOUNDATIONS AND STRUCTURE

Reinforced concrete with separate footings and one way slabs.

EXTERIOR BRICKWORK

• Ceramic brick walls (exterior part - 12 cm) with air compartment and high density polystyrene insulation (8 cm) and thermal clay block (19 cm).

ROOF

• Flat non-trafficable roof with XPS insulation (8 cm) and trafficable solarium with tiles accessible through a concrete stair.

FAÇADE

Single layer mortar with a scraped finish. In white color.

INTERNAL WALLS

• Brick walls with plaster finish.

BATHROOM FINISHES

• Top of the range "Gres" ceramics according to interior design. Decorative gres Seawood model in the sink wall.

INTERIOR AND EXTERIOR FLOORING

- Interior, Top of the range "Gres" ceramic tiles with white aluminum profile (U-shaped) on floor and ceiling as a baseboard. Maryland natural Model.
- Exterior, Top of the range "Gres" anti-slip ceramic tiles of the same range as interior floor tiles.
 Maryland natural Model.

INTERIOR AND EXTERIOR LIGHTING

- Interior, LED recessed lights, switches in white colour throughout, plugs according to standard regulations.
- Exterior, façade fixtures, LED type lighting. Garden lighting.

EXTERIOR CARPENTRY

- Aluminum, with European mark and thermal break.
- Motorized blinds in bedrooms, in grey colour.